

40C50

This paint pump is the perfect pump for Airless® applications.

- Ideal for Airless applications
- High efficiency pump for maximum energy savings
- Optimized construction for simple & quick maintenance

PRODUCTIVITY FOR ALL



Configuration of the 40C50 Airless paint pump

Set-up	Suction rod (ø 25)	Drain rod	Atomizing air regulator	Fluid pressure regulator	Filter pump outlet	Part number
40C50 bare pump	M26x125	-	-	-	-	144.148.150
Wall mounted	-	-	-	✓	-	151.775.050
Wall mounted	✓	✓	-	✓	-	151.775.100
Wall mounted	-	✓	-	✓	✓	151.775.150
Wall mounted	✓	✓	-	✓	✓	151.775.200
2 arm cart mounted	✓	✓	-	✓	✓	151.775.400

Maintenance kits

Description	Part number
Seals kit - 1000-4 air motor	146.270.991
Servicing kit - 1000-4 air motor	146.270.995
Seals kit - C50 with upper Polyfluid & lower GT	144.950.091
Servicing kit - C50 with upper Polyfluid & lower GT	144.950.096
Seals kit - C50 with upper & lower GT	144.950.090
Servicing kit - C50 with upper & lower GT	144.950.095

Accessories

Description	Part number
Two Post Cart w/o plate	051.221.000
Two Post Pump Mounting Plate	056.100.199
Easyflow suction rod Ø25 plunging tube length 600 mm	149.596.150
Easyflow suction rod Ø25 plunging tube length 1000mm (for 200 liters drums)	149.596.160
Stainless steel flushing rod F18 x 125	049.596.000
Filter	155.580.400

Spray guns

Pumps

Machines & Controllers

Accessories

General informations