

# 40F100



This Flowmax® pump is recommended for feeding 2 guns.

- Flowmax® technology for zero maintenance
- Designed for moisture-sensitive and abrasive materials
- Extended lifetime

LUB FREE PUMP ENSURES TOTAL SEALING AND RELIABILITY



## Configuration of the 40F100 Flowmax® paint pump

Set-up	Suction rod (Ø25)	Drain rod	Air regulator Fluid pressure	Pump output filter	Part number
Bare pump	-	-	-	-	151.786.000
Wall mounted	✓	-	✓	-	151.786.100
Wall mounted	✓	✓	✓	✓	151.786.200
2 arm cart-mounted	✓	✓	✓	✓	151.786.400

## Maintenance kits

Description	Part number
Seal kit for 2000-4 air motor	146.270.990
Repair kit for 2000-4 air motor	146.270.996
Seal kit for F100 hydraulic section	144.960.291
Repair kit F100 hydraulic section	144.960.292

## Accessories

Description	Part number
Two Post Cart w/o plate	051.221.000
Two Post Pump Mounting Plate	056.100.199
Easyflow suction rod Ø25 plunging tube length 600 mm	149.596.150
Easyflow suction rod Ø25 plunging tube length 1000mm (for 200 liters drums)	149.596.160
Stainless steel flushing rod F18 x 125	049.596.000
1 arm cart	051.730.110
Fluid filter	155.580.400
Gravity hopper 6 liters	151.140.250